

TECHNICAL SHEET




SUNBRELLA PLUS

Boat equipment

CHARACTERISTICS	VALUES		UNITS	STANDARDS
	WARP	WEFT		

OVERALL CHARACTERISTICS

Composition	100 % Sunbrella solution dyed acrylic			
Finish	Resin based anti-fungi coating, water and UV resistant.			
Weave	Canvas			ISO 7211-1
Weight	320		g/m ²	ISO 2286-1
Width	152		cm	EN 1773

FABRIC STRENGTH

Oil-repellent properties	5		class /8	ISO 14419
Tensile strength	145	90	daN	ISO 13934-1
Tear strength	3.3	2.1	daN	ISO 13937-1
Elongation at break	37	32	%	ISO 13934-1
Schmerber	1200		mm	ISO 811
Spray test	4-5		class /5	ISO 4920
Air permeability	3.4		l/m ² /s	ISO 9237

COLOUR RESISTANCE

Colour fastness UV	7-8		class /8	ISO 105 B02
Colour fastness weather condition	7-8		class /8	ISO 105 B04
Colour fastness under dry friction	5		class /5	ISO 105X12
Colour fastness under wet friction	5		class /5	ISO 105X12

USE

Roll length	50		lm	
Recommended use	Cockpit cover, spray hood, bimitop, sun awning, flybridge, winter cover			
Guarantee	5		Years	

The values for this product may have a variation of +/-5%.

SUNACRYL[®]
OUTDOOR FIBRE
by DICKSON

FINISHING
CLEANGARD[®]
OUTDOOR TREATMENT
by DICKSON



WARRANTY
5
YEARS



MADE IN

FRANCE

Dickson - Constant

10, rue des Châteaux - BP 109 - Z.I la Pilaterie 59443 Wasquehal cedex - France
Tél. : +33.(0)3.20.45.59.59 - Fax : +33.(0)3.20.45.59.00 - www.dickson-constant.com